

PORTABLE DIESEL PUMP PACKAGES

POWERED BY: **KOHLER** Diesel



* ML3KEADHD with Optional Accessories Shown

Portable Pump Specifications

- Kohler Heavy Duty Industrial Air Cooled Diesel Engine with Threaded Shaft
- IPT Impeller and Volute by Gorman Rupp
- Recoil or Electric Start
- Roll Bar Skid
- NPT Threaded Connections
- Steel Suction Strainer Included
- Self Primes to Over 20ft with Built in Buna Check Valve
- Stainless Steel Shaft Sleeve
- Fuel Tank
- Engine Oil Included
- Fuel and Oil Filters
- Shop Tested
- 3 Year Engine Warranty

Physical Properties

Model	Starting	Weight	Length	Width	Height
ML2FP350	Electric	156	31	22	23
ML3KEADHD	Electric	200	31	22	24
ML3KRADHD	Recoil	200	31	22	24
ML4KEADHD	Electric	228	31	22	24
ML4KRADHD	Recoil	228	31	22	24
ML6TP-SM	Electric	975	40	33	71

Model	Suction / Discharge	Shaft size, Threaded	Max Flow (GPM)	Max Head (Feet)	Max Solids Handling	Max Lift (Feet)	Max Working Pressure
ML2FP350	2 NPT	5/8"	130	250	N/A	26	108 psi
ML3KEADHD	3 NPT	1"	340	100	2"	20	60 psi
ML3KRADHD	3 NPT	1"	340	100	2"	20	60 psi
ML4KEADHD	4 NPT	1"	530	102	2"	26	26 psi
ML4KRADHD	4 NPT	1"	530	102	2"	26	26 psi
ML6TP-SM	6 NPT	1"	1,000	96	3"	20	60 psi

Optional Accessories

- 2 Wheel Dolly Kit for Roll Bar Skid
- Hose Kit
- Spark Arrestor
- Emergency Air Intake Shutdown
- Battery and Battery Cables
- Contact us for custom accessory options

M&L Engine, LLC
 1212 Saint Charles St.
 Houma, LA 70360
 (985) 857-8000
 (800) 960-0068



www.mlengine.com email: sales@mlengine.com