

PORTABLE DIESEL PUMP PACKAGES

POWERED BY: YANMAR DIESEL



* ML3YEADHD with Optional Accessories Shown

Portable Pump Specifications

- Yanmar Industrial Air Cooled Diesel Engine with Threaded Shaft
- IPT Cast Aluminum Pump by Gorman Rupp with Cast Iron Wear Parts
- Recoil or Electric Start
- Roll Bar Skid
- NPT Threaded Connections
- Suction Strainer Included
- Fuel Tank
- Engine Oil Included
- Fuel and Oil Filters
- Shop Tested
- 2 Year / 2000 Hour Engine Warranty

Physical Properties

Model	Starting	Weight	Length	Width	Height
ML2YRAD	Recoil	146	31	22	24
ML3YRAD	Recoil	146	31	22	24
ML3YEADHD	Electric	190	31	23	24
ML3YRADHD	Recoil	190	31	23	24
ML4YEADHD	Electric	230	31	24	24
ML4YRADHD	Recoil	230	31	24	24
ML6YELDHD	Electric	1714	103	53	72

Model	Suction / Discharge	Shaft size, Threaded	Max Flow (GPM)	Max Head (Feet)	Max Solids Handling	Max Lift (Feet)	Max Working Pressure
ML2YRAD	2 NPT	3/4"	240	125	1-1/4 "	26	TBA
ML3YRAD	3 NPT	3/4"	290	110	1-1/4"	26	TBA
ML3YEADHD	3 NPT	1"	340	100	2"	20	60 psi
ML3YRADHD	3 NPT	1"	340	100	2"	20	60 psi
ML4YEADHD	4 NPT	1"	530	102	2"	26	60 psi
ML4YRADHD	4 NPT	1"	530	102	2"	26	60 psi
ML6YELDHD	6 NPT	N/A	1,000	96	3"	20	60 psi

Optional Accessories

- 2 Wheel Dolly Kit for Roll Bar Skid
- Hose Kit
- Spark Arrestor
- Emergency Air Intake Shutdown
- Battery and Battery Cables
- Contact us for custom accessory options

M&L Engine, LLC
 1212 Saint Charles St.
 Houma, LA 70360
 (985) 857-8000
 (800) 960-0068



www.mlengine.com email: sales@mlengine.com